



Discomix



Performance and high output.

**Weight & speed
for a better work.**

For tractors from:
110 - 200 HP





Discomix is a fast stubble disc harrows with independent discs designed for its versatility and its performance. Discomix is an ideal tool for the mixing of the stubble surface and the preparation for drilling. This range of fully mounted implements are compact and handy, which ensures a high level of output, while having a low power requirement.

Discomix range is available in fixed version (3,00 or 4,00m) or folding : Discomix R (4,00, 5,00 and 6,00 m).

To ensure an optimal finish, a broad choice of rollers and harrows are available (option).

An original combination for a better versatility



The system of shock absorber "Roll' choc" makes it possible to absorb the shocks and to follow with precision the relief of the ground. This rubber shock absorber is simple and no maintenance.



Discomix is equipped with notched discs 620 mm in diameter with flat profile (Roll' Coup) assembled in pairs on the same shaft.

With a specific working angle, work carried out is regular all over the width of the Discomix.



The rear roller controls the working depth, presses the ground and leaves a level finish.

A broad choice of rollers are available in option.

A wide choice of rear accessories



A row of harrows is available (option). Located between the two disc gangs. The soil and residues are projected against the harrows which ensure an even distribution of the residues and a crumbling of the clods of earth.



Twin roller



« U » roller








Twin & U roller



Triple following harrows

Technical features

				
Discomix				
24	3,00 m	3,00 m	1 850 kg	110 HP
32	4,00 m	4,00 m	2 110 kg	120 HP
Discomix R				
32	4,00 m	3,00 m	3 250 kg	120/140 HP
40	5,00 m		3 550 kg	150/180 HP
48	6,00 m		3 970 kg	180/210 HP

Rear equipments (Option)

Models	Diameter	Width
Crumbler roller	Ø 500 mm Ø 600 mm	3,00 - 6,00 m
Twin roller	Ø 500 mm	3,00 - 6,00 m
« U » roller	Ø 500 mm	3,00 - 6,00 m
Triple harrows	700mm Ø 14 mm	3,00—6,00 m

Authorized dealer

